

## C3-100



### ➔ C3 100 - Door Access Control

Number of Doors Controlled : 1 Door

Number of Readers Supported : 2 ( 26-bit wiegand reader)

Types of Readers Supported : 26-bit Wiegand, others upon request

Number of Inputs :2( 1 Exit Button, 1 Door Sensor)

Number of Outputs : 2 (1-From C Relay for Lock and 1-Form C Relay for Aux Output)

Card Holders Capacity : 30,000

Log Events Capacity : 100,000

Weight : 7.4lbs (3.35kg)

Communication : TCP/IP and RS-485

Enclosure : Powder Coated Aluminium

Mounting : Wall Mount

Recommended Power Supply : 12V DC, 1.5A

Dimensions (Bundle Only) : 380mm(L)X80mm(W) X 280mm(H)

Dimensions ( Board Only) : (160mm×106mm)

#### Features:

- ▶ TCP/IP and RS485 communication
- ▶ Built-in Auxiliary input and Output
- ▶ Advanced Access Control Functions
- ▶ Support full range of card readers

#### Software and Database Supported :

1. Access Security System 5.2.22.12132  
(Web Base Database Type :- My SQL / MS SQL)
2. Access Security System 3.5 (Desktop Version) Database Type:- MS Access / MS SQL